## $\texttt{BOUTLANDER}^{\mathsf{M}}$ MAX XT 570 T3

## HIGHLIGHTS

- Rotax<sup>®</sup> V-Twin engine
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS<sup>™</sup>)
- 1,361 kg WARN  $^{\scriptscriptstyle \dagger}$  winch with roller fairlead
- Heavy-duty front and rear bumpers
- Painted plastics for premium look
- 12-in. cast-aluminum wheels
- 25-in. Maxxis<sup>†</sup> M923J radial tires
  Torsional Trailing arm Independent (TTI)
- rear suspension
   Wind deflectors
- Wind deflectors

- Steel racks with LinQ quick-attach accessory system and a combined 163.3 kg capacity
- 10.9 L water-resistant rear compartment
- Dynamic passenger comfort ergonomics
- Multiposition passenger handgrips
- Raised floorboards



ENGINE	570	
Туре	Rotax 570 cc V-twin, liquid cooled	
Fuel Delivery System	Electronic Fuel Injection (EFI)	
Transmission	CVT, P / R / N / H / L, standard engine braking	
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE <sup>‡</sup> auto-locking front differential	
Power Steering	Tri-Mode Dynamic Power Steering (DPS)	

<b>SUSPENSIONS</b>		
Front Suspension	Double A-arm 22.9 cm travel	
Front Shocks	Oil	
Rear Suspension	Torsional Trailing arm Independent (TTI) 22.4 cm travel	
Rear Shocks	Oil	
BRAKES		
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers	

Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

## Pure Magnesium

.S
Maxxis M923J 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm)
Maxxis M923J 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm)
12-in. cast-aluminum

DIMENSIONS / CAPACITIES				
LxWxH	231 x 116.8 x 133 cm			
Wheelbase	149.9 cm			
Ground Clearance	26.7 cm			
Seat Height	85.8 cm			
Dry Weight*	336 kg			
Rack Capacity	Front: 54.4 kg Rear: 109 kg			
Storage Capacity	Rear: 10.9 L			
Towing Capacity	750 kg trailer with brakes and 590 kg trailer without brakes			
Fuel Capacity	20.5 L			

Gauge	Multifunction Digital: Speedometer, tachometer, odometer,	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
	trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Lighting	70 W from dual 35-W front light / brake light
Winch	1,361 kg WARN winch with roller fairlead	Seat	Seat with backrest
Protection	Heavy-duty front & rear bumpers Handlebar wind deflectors	Anti-theft System	Digitally Encoded Security System (D.E.S.S.)
T3 features	Seat with backrest, lockable fuel cap, transmission lockable in park mode (P), towing hitch and trailer plug, two front position lamps + directional indicators, extra tail light / brake light + directional indicators, mirrors, horn		

## WARRANTY

Factory

Rear

2 years

©2017 Bombardier Recreational Products Inc (BRP). All rights reserved. <sup>TM,®</sup> and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP US Inc. "Base model dry weight shown. "Visco-Lok is a trademark of GRN Viscodrive GmbH. 'All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsible, BRP hight recommends that all ATV drivers take at training course. For safety and training information, see your dealer or, in U.S.A. call the ATV Safety Institute at 1 (610) 739-1535 ext 227. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. *Ava* decessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.

