≋OUTLANDER[™] 6x6 DPS[™] 650 T3

HIGHLIGHTS

- Rotax[®] V-twin engine
- Continuously Variable Transmission (CVT) with Extra Low L-gear
- 318 kg capacity Dual-Level[™] cargo box with modular accessories
- 750 kg towing capacity
- Tri-Mode Dynamic Power Steering (DPS)
- Double Torsional Trailing arm Independent (TTI2) rear suspension
- Double A-arm front suspension with dive-control geometry
- 1,361 kg WARN † winch with roller fairlead

- Relocated air intakes
- Quick release sway bar
- High-strength, multifunction racks with LinQ[™] quick-attach accessory system
- Digitally Encoded Security System (D.E.S.S.™)



ENGINE	650	
Туре	Rotax 649.6 cc V-twin liquid cooled	
Fuel Delivery System	Electronic Fuel Injection (EFI)	
Transmission	CVT, P / R / N / H / Extra Low L, standard engine braking	
Drive Train	Selectable 4WD / 6WD with Visco-Lok [‡] QE auto-locking front differential	
Power Steering	Tri-Mode Dynamic Power Steering (DPS)	

SUSPENSIONS

Front Suspension	Double A-arm 22.9 cm travel		
Front Shocks	Oil		
Rear Suspension	Double Torsional Trailing arm Independent (TTI2) with quick-release sway bar 23.6 cm travel		
Rear Shocks	Oil		
BRAKES			
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers		
Rear	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers		

Green

TIRES / WHEELS				
Front Tires	Carlisle† Badland 26 x 8 x 12 in. (660 x 203 x 305 mm)			
Rear Tires	Carlisle Badland 26 x 10 x 12 in. (660 x 254 x 305 mm)			
Wheels	12-in. black steel			

DIMENSIONS / CAPACITIES				
LxWxH	312 x 124 x 126 cm			
Wheelbase	208.1 cm			
Ground Clearance	27.9 cm			
Seat Height	87.7 cm			
Dry Weight*	515 kg			
Rack Capacity	Front: 45 kg Rear: 318 kg			
Storage Capacity	Dual-level cargo box with modular accessories Rear: 70 L			
Towing Capacity	750 kg			
Fuel Capacity	20.5 L			

FEATURES			
Gauge	Multifunction Digital: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
		Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
		Seat	Seat with backrest
Winch	1,361 kg WARN winch with roller fairlead	Anti-theft System	Digitally Encoded Security System (D.E.S.S.)
T3 features	Seat with backrest, lockable fuel cap, transmission lockable in park mode (P), towing hitch and trailer plug, two front position lamps + directional indicators, extra tail light / brake light + directional indicators, mirrors, horn		

WARRANTY

Factory

2 years

©2017 Bombardier Recreational Products Inc (BRP). All rights reserved. ^{TM,®} and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP US Inc. "Base model dry weight shown. "Visco-Lok is a trademark of GRN Viscodrive GmbH. 'All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsible, BRP hight recommends that all ATV drivers take at training course. For safety and training information, see your dealer or, in U.S.A. call the ATV Safety Institute at 1 (610) 739-1535 ext 227. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. *Ava* decessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.



BRP

Can-AmOffroad.com