# **§MAVERICK™ X3 X™rs TURBO R**

## DEFIANT

- Trademark Can-Am DNA with
  Industry leading 172 hp next generation design
- Low seating position
- Ergo-Lok cockpit with fourway adjustable seats

## **POWERFUL**

- turbocharged and intercooled Rotax® ACE engine
- Advanced airflow dynamics
- QRS-X transmission

#### **PRECISE**

- TTX suspension with industry leading travel
- Ultra efficient and lightweight chassis
- Sharpest handling features



Platinum Satin

#### SPECIFIC TO X rs PACKAGE

- 72 in. (182.9cm) wide
- 14-in. aluminum beadlock wheels with 30-in. Maxxis Bighorn<sup>†</sup> 2.0 tires
- Up to 24-in. (61 cm) of suspension travel
- Fully adjustable FOX<sup>†</sup> 3.0 PODIUM RC2<sup>†</sup> remote reservoir shocks with bypass
- Full roof, heavy-duty HMW skid plate and 4-point harness
- Painted color

ENGINE	TURBO R
Туре	172 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc Turbocharged Triple-cylinder engine, liquid cooled with integrated intercooler and Donaldson† high-performance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System X (QRS-X) CVT with high airflow, L / H / N / R/ P
Drive Train	Selectable 2WD / 4WD with Visco-Lok <sup>‡</sup> X auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS™)

SUSPENSIONS	
Front Suspension	Trophy truck inspired Double A-arm with sway bar 22 in. (55.9 cm) travel
Front Shocks	FOX 2.5 PODIUM RC2 Piggyback with bypass, dual speed compression and rebound adjustments
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar 24 in. (61 cm) travel
Rear Shocks	FOX 3.0 PODIUM RC2 remote reservoir with bypass, dual speed compression and rebound adjustments

BRAKES	
Front	Dual 262 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 248 mm ventilated disc brakes with hydraulic twin-piston calipers

<b>TIRES / WHEEL</b>	<b>S</b>
Front Tires	Maxxis Bighorn 2.0 30 x 10 x 14 in. (76.2 x 25.4 x 35.6 cm)
Rear Tires	Maxxis Bighorn 2.0 30 x 10 x 14 in. (76.2 x 25.4 x 35.6 cm)
Wheels	14-in. aluminum beadlock

DIMENSIONS / CAPACITIES				
LxWxH	335.3 x 182.9 x 170.2 cm			
Wheelbase	259.1 cm			
<b>Ground Clearance</b>	38.1 cm			
Estimated Dry Weight	720.9 kg			
Cage / Chassis	Dual-phase 980 steel, fully welded			
Rack Capacity	91 kg with LinQ™ quick-attach			
Storage Capacity	Total: 9.4 L Glove box: 6.2 L Center console: 2.8 L Cup holders: 0.4 L			
Fuel Capacity	40 L			

<b>FEATURES</b>			
Gauge	Multifunction Analog / Digital: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, sport / ECO™ mode, seat	Protection	Integrated front bumper, heavy-duty full High Molecular Weight (HMW) skid plate, quarter-doors, full roof and 4-point harness
	belt and 4 x 4 indicator, diagnostics, clock, auto shut off	Instrumentation	Lighter type DC outlet in central console
		Lighting	LED headlights and tail lights with unique Can-Am LED signature
Winch	N/A	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/ Stop button

WARRANTY	
Factory	2 years
Extended	Up to 30 months B.E.S.T. coverage





